

LS 수평제어 실린더

A

[10-1] E380/R39/45/C45/I30/R43/R48/R45HST/R53/LT360D

N0620035



A	B	최소길이	D	E
27	45	435	20	39

B

[10-2] E/U/SN/N

N0620036



A	B	최소길이	D	E
41	60	425	19	38

B

[10-3] 피아트55-66

N0620036



A	B	최소길이	D	E
42	66	440	28	52

C

[10-4] 피아트80-66/TD70/TD80/TD90

N0620037



A	B	최소길이	D	E
42	65	485	26	57

C

[10-5] TN75/TN85/PS80/PS100

N0620037



A	B	최소길이	D	E
42	65	475	28	52

LS 수평제어 실린더

C

[11-1] L65/L85

N0620037



A	B	최소길이	D	E
41	60	450	29	61

B

[11-2] L7020/7030/7040

N0620036



A	B	최소길이	D	E
42	66	430	28	52

C

[11-3] TL100/80/T5060/피아트90-110

N0620037



A	B	최소길이	D	E
42	66	485	35	67

D

[11-4] T6020

N0620038



A	B	최소길이	D	E
46	78	635	40	71

A

[11-5] KR45/50/55/TR/TX

N0620035



A	B	최소길이	D	E
42	59	400	20	42

LS 수평제어 실린더

E

[12-1] T6070/6080

N0620039



A	B	최소길이	D	E
46	78	610	35	66

E

[12-2] TM125/TM130/TM155

N0620039



A	B	최소길이	D	E
46	78	600	35	66

E

[12-3] TX110/T6050/T6040

N0620039



A	B	최소길이	D	E
45	76	675	39	70

D

[12-4] P7197

N0620037



A	B	최소길이	D	E
35		515(530)	28	52

국제 수평제어 실린더

A

[13-1] F/AF/A4800/A5700

N0620035



A	B	최소길이	D	E
36		400	21	39

A

[13-2] 4715N

N0620035



A	B	최소길이	D	E
42		400	21	39

C

[13-3] JD5310/5300/5400

N0620037



A	B	최소길이	D	E
35		420	29	52

C

[13-4] 5805/A5800/A6500

N0620037



A	B	최소길이	D	E
35		460	29	54

C

[13-5] JD5325/5425/5525/1650K/1750K/KX100/7505/8205/9205/LUXEN시리즈

N0620037



A	B	최소길이	D	E
35		460	29	54

C

[13-6] JD6120/6220/6230/6330

N0620037



A	B	최소길이	D	E
35		615	40	75

국제 수평제어 실린더



[14-1] JD6430/6520/6610 JD115ps

N0620037



A	B	최소길이	D	E
35		640	40	75



[14-2] JD6830/6930/7230/7330

N0620039



A	B	최소길이	D	E
35		854	41	80



[14-3] JD6125/6140/6150

N0620039



A	B	최소길이	D	E
35		870	41	80



[14-4] JD6630/6620 JD125ps/R,M시리즈

N0620039



A	B	최소길이	D	E
35		650(750)	40	72

대동 수평제어 실린더

A

[15-1] D380/LX480/DK550/ES500V/NS580

N0620035



A	B	최소길이	D	E
34	51	365	20.5	38.5

A

[15-2] D4351(Φ22)/L3503(Φ19)/L300/L3301

N0620035



A	B	최소길이	D	E
40		385	20	38

A

[15-3] D500

N0620035



A	B	최소길이	D	E
32.5	50	435	20	38

A

[15-4] NX520/470/430/D400/450/470

N0620035



A	B	최소길이	D	E
32.5	50	435	20	38

B

[15-5] RX560/530/RX570

N0620036



A	B	최소길이	D	E
35		420	24.5	48

B

[15-6] D52/55/58/62/RX730

N0620036



A	B	최소길이	D	E
32.5		470	38	54

대동 수평제어 실린더



[16-1] 대동 D85/852/70/PX800~1000/MX70~100

N0620037



A	B	최소길이	D	E
42		510	30	60



[16-2] JD6230

N0620037



A	B	최소길이	D	E
35		615	40	75



[16-3] JD6430

N0620037



A	B	최소길이	D	E
35		640	40	75



[16-4] JD6830/6930

N0620039



A	B	최소길이	D	E
35		854	41	80

동양 수평제어 실린더

A

[17-1] T480(구)/350(구)

N0620035



A	B	최소길이	D	E
41		415	20	38

A

[17-2] T480(신)/T302/T352/T403/T453/T483/G시리즈/TE58

N0620035



A	B	최소길이	D	E
42	59	400	20	42

B

[17-3] T550(구)/TA5240

N0620036



A	B	최소길이	D	E
35		465	20	38

B

[17-4] T550(신)/680/502/552/T503/T553/T623/T720(S)/TX703

N0620036



A	B	최소길이	D	E
42	66	435	25	50

C

[17-5] T860/사매80

N0620037



A	B	최소길이	D	E
45	77	600	28	52

C

[17-6] 도라도70/76

N0620037



A	B	최소길이	D	E
41	65	480	29	61



[18-1] MAX110/120

N0620037



A	B	최소길이	D	E
21		505	38	69



[18-2] T803/903/1003/JX시리즈/TS시리즈

N0620037



A	B	최소길이	D	E
42	66	485	35	67



[18-3] MAX130/125

N0620039



A	B	최소길이	D	E
47	78	630	40	72



[18-4] 펜트130/150마력

N0620039



A	B	최소길이	D	E
36		645	62	100

구보다 수평제어 실린더

A

[19-1] 구보다 소형

N0620035



A	B	최소길이	D	E
36		400	21	39

B

[19-2] M7040/M7060

N0620036



A	B	최소길이	D	E
35		430	25.5	49

C

[19-3] M9540(M5-86)

N0620037



A	B	최소길이	D	E
35		515	28	52

안마 수평제어 실린더

A

[19-4] 안마소형

N0620035



A	B	최소길이	D	E
36		400	21	39

아세아 수평제어 실린더

B

[20-1] ST440,445

N0620036



A	B	최소길이	D	E
35		465	20	38

E

[20-2] MF6465

N0620039



A	B	최소길이	D	E
35		600	34	66

C

[20-3] MF4445,5460

N0620037



A	B	최소길이	D	E
35		600	36	67

조향 실린더

피아트 55-66 조향실린더 TK 12015

포드 7811/6611 조향실린더 TK140212

